

ASMACO WINDOW & DOOR ALL SEASON PU FOAM

Safety Data Sheet

According to Regulation (EC) No.1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1. Product Identifier

Product Name: PU FOAM MANUAL AND GUN TYPE
Trade Name: ASMACO ALL SEASON POLYURETHANE FOAM 850, 750, 650, 500, 330 ml
Type of Product: One Component polyurethane foam

1.2. Relevant identified uses of the substance or mixture uses advised against

Identified Uses: Polyurethane foam.
Intended for general public.
Main use category Industrial use, Consumer use, Professional use, Construction use,
Uses advised against: No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Manufacturer: Anchor Allied Factory LLC
P. O. Box. 21152, Sharjah, UAE.
Telephone Number: +9716 5342091
E-mail: info@anchorallied.com
Website: www.anchorallied.com

1.4. Emergency telephone number

Emergency Telephone Number: +9716 5342091
Fax No: +9716 5342107

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Product definition: Mixture
Classification according to Regulation (EC) No.1272/2008 [CLP]

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurized container: May burst if heated.
Carc.	category 2	H351: Suspected of causing cancer.
Lact.	-	H362: May cause harm to breast-fed children.
Acute Tox.	category 4	H332: Harmful if inhaled.
STOT RE inhaled.	category 2	H373: May cause damage to organs through prolonged or repeated exposure if
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H335: May cause respiratory irritation.
Skin Irrit.	category 2	H315: Causes skin irritation.
Resp. Sens.	category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens.	category 1	H317: May cause an allergic skin reaction.
Aquatic Chronic	category 4	H413: May cause long lasting harmful effects to aquatic life.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008[CLP]

Hazard pictogram [CLP]



GHS02



GHS07



GHS08

Signal word (CLP) Danger

ASMACO WINDOW & DOOR ALL SEASON PU FOAM

Safety Data Sheet

According to Regulation (EC) No.1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Product identifier: Contains: Polymeric MDI, Alkanes, C₁₄₋₁₇ chloro.

Hazard statements (CLP)

H222 Extremely flammable aerosol.
H229 Pressurized container: May burst if heated.
H351 Suspected of causing cancer.
H362 May cause harm to breast-fed children.
H332 Harmful if inhaled.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H315 Causes skin irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements (CLP)

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P308 + P313 IF exposed or concerned: Get medical advice/attention.
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

Supplemental information -

Persons already sensitized to diisocyanates may develop allergic reactions when using this product. - Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. - This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i. e. type A1 according to standard EN 14387) is used.

Other hazards

No information available

SECTION 3. COMPOSITION AND INFORMATION ON INGREDIENTS:

3.1. Substances

Not Applicable.

3.2. Mixtures:

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Ingredient	Registration number	CAS No.	EC No.	Conc. (%w/w)	Hazard Class and Category	Hazard Statement
Dimethyl ether	01-2119472128-37-0002	115-10-6	204-065-8	2-10	Press. Gas, Flam. Gas 1	H220
Diphenylmethane diisocyanate isomers and homologues	-----	9016-87-9	618-498-9	25-40	Acute Tox. 4 (Inhalation), Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Sens. 1, Carc. 2, STOT SE 3, STOT RE 2,	H332 H315, H319, H334, H317, H351, H335, H373
Alkanes, C ₁₄₋₁₇ chloro,	01-2119519269-33	85535-85-9	287-477-0	< 35	Lact. ; Aquatic Acute 1; Aquatic Chronic 1;	H362, H400, H410
Propane	01-2119486944-21	74-98-6	200-827-9	3-10	Press. Gas, Flam. Gas 1	H220
n-Butane	01-2119474691-32	106-97-8	203-448-7	5-10	Press. Gas Flam. Gas 1	H220
Isobutane	01-2119485395-27	75-28-5	200-857-2	2-5	Press. Gas Flam. Gas 1	H220

ASMACO WINDOW & DOOR ALL SEASON PU FOAM

Safety Data Sheet

According to Regulation (EC) No.1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 4. FIRST AID MEASURES:

4.1. Description of first aid measures General:

GENERAL.

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with labored breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

After inhalation: Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact: Wash immediately with lots of water. Take victim to a doctor if irritation persists.

After eye contact: Rinse immediately with plenty of water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

After ingestion: Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Consult a doctor/medical service if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation: Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Runny nose. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible inflammation of the respiratory tract. Risk of lung oedema. Respiratory difficulties.

After skin contact: Tingling/irritation of the skin.

After eye contact: Irritation of the eye tissue. Lacrimation.

After ingestion: Not applicable.

4.2.2 Delayed symptoms No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available, it will be listed below.

SECTION 5. FIRE FIGHTING MEASURES:

5.1. Extinguishing media foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

Aerosols may explode if heated above 50°C Forms hazardous decomposition products CO, CO₂

5.3. Advice for firefighters Keep container(s) exposed to fire cool, by spraying with water. In case of fire, do not breathe fumes

SECTION 6. ACCIDENTAL RELEASE MEASURES:

Personal Precautions: Use appropriate safety equipment. For additional information, refer to item 8, Exposure Controls and Personal Protection.

Environmental Precautions: Do not allow to enter sewers/surface or ground water.

Cleaning/Collecting Precautions: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleaning agents.

SECTION 7. HANDLING AND STORAGE:

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Observe very strict hygiene - avoid contact. Remove contaminated clothing immediately.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Keep out of direct sunlight. Store in a dry area. Ventilation at floor level. Fireproof storeroom. Unauthorized persons are not admitted. Meet the legal requirements. Max. storage time: 1 year(s).

7.2.2 Keep away from: Heat sources, ignition sources, (strong) acids, (strong) bases.

7.2.3 Suitable packaging material: Aerosol.

7.2.4 Non suitable packaging material: No data available

ASMACO WINDOW & DOOR ALL SEASON PU FOAM

Safety Data Sheet

According to Regulation (EC) No.1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

7.3. Specific end use(s) If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION:

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

EU

Dimethyl ether	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1000 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1920 mg/m ³

Belgium

Hydrocarbures aliphatiques sous forme gazeuse : (Alcanes C1-	Time-weighted average exposure limit 8 h	1000 ppm
Oxyde de diméthyle	Time-weighted average exposure limit 8 h	1000 ppm
	Time-weighted average exposure limit 8 h	1920 mg/m ³

Germany

Chloralkane, C14-17 (Chlorierte Paraffine C14-17)	Time-weighted average exposure limit 8 h (TRGS 900)	0.3 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	6 mg/m ³
Dimethyl ether	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1900 mg/m ³
Isobutane	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m ³
Propane	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m ³
	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
pMDI	Time-weighted average exposure limit 8 h (TRGS 900)	0.05 mg/m ³

UK

Dimethyl ether	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	766 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	958 mg/m ³
Isocyanates, all (as-NCO) except methyl isocyanate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	0.02mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	0.07mg/m ³

USA (TLV-ACGIH)

Butane, all isomers	Short time value (TLV-Adopted value)	1000 ppm
---------------------	--------------------------------------	----------

b) National biological limit values

If limit values are applicable and available these will be listed below

8.1.2 Sampling Methods

If applicable and available, it will be listed below.

Isocyanates	NIOSH	5521
Isocyanates	NIOSH	5522

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available, these will be listed below.

8.1.4 DNEL/PNEC Values

Alkanes, C₁₄₋₁₇, Chloro	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	47.9mg/kg bodyweight/day
Long-term - systemic effects, inhalation	6.7 mg/m ³

ASMACO WINDOW & DOOR ALL SEASON PU FOAM

Safety Data Sheet

According to Regulation (EC) No.1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

DNEL/DMEL (General population)	
Long-term - systemic effects, oral	0.58 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2 mg/m ³
Long-term - systemic effects, dermal	28.7 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	1 µg/l
PNEC aqua (marine water)	0.2 µg/l
STP	80 mg/l
PNEC sediment (freshwater)	13 mg/kg dwt
PNEC sediment (marine water)	2.6 mg/kg dwt
PNEC soil	11.9 mg/kg dwt
PNEC Oral	10 mg/food

8.1.5 Control banding

If applicable and available, it will be listed below

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex.

Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe very strict hygiene - avoid contact. Do not eat, drink or smoke during work.

a) Respiratory protection:

Wear gas mask with filter type A if conc. in air > exposure limit.

b) Hand protection:

Gloves.

Materials	Break through time	Thickness
LDPE (Low Density Polyethylene)	10 minutes	0.025mm

c) Eye protection:

Protective goggles

d) Skin protection:

Head/neck protection. Protective clothing.

8.2.3. Environmental exposure controls

Avoid release to the environmental

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES:

9.1. Information on basic physical and chemical properties

Appearance: physical state:	Liquid in Aerosol tin can.
Color:	Variable in colors, depending on the composition.
Odor:	Characteristics odor
Odor threshold:	No data available
Particle size:	Not applicable
Explosion limits:	No data available
Flammability:	Extremely flammable aerosol
Log Kow:	No applicable (mixture)
Dynamic viscosity:	No data available

ASMACO WINDOW & DOOR ALL SEASON PU FOAM

Safety Data Sheet

According to Regulation (EC) No.1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Kinematic viscosity:	No data available
Melting point:	No data available
Boiling point/range:	No data available
Flash point:	No data available
Evaporation rate:	No data available
Vapor pressure:	6 bar (@ 20°C).
Relative density:	0.95 g/cm ³ (@ 20°C).
Solubility in water:	Insoluble in water
Auto-ignition:	Not available.

9.2. Other information

None

SECTION 10. STABILITY AND REACTIVITY:

10.1. Reactivity

May be ignited by sparks. Gas/vapor spreads at floor level: ignition hazard. No data available.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

May polymerize with many compounds e.g.: (strong) bases and amines. Reacts violently with (some) acids/bases.

10.4. Conditions to avoid

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

(strong) acids, (strong) bases.

10.6. Hazardous decomposition products

On heating: release of toxic/combustible gases/vapors (hydrogen cyanide). On burning release of toxic and corrosive gases/vapors (nitrous vapors, hydrogen chloride, carbon monoxide - carbon dioxide).

SECTION 11. TOXICOLOGICAL INFORMATION:

11.1. Information on toxicological effects:

No data available on the mixture

Polyethylene polyphenyl isocyanate	
LD50 oral rat	10000 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 Dermal Rabbit	> 500mg/kg
LD50 Inhalation - Rat	10 mg/l 4 h
Inhalation	Category 4

Alkanes, C14-17, chloro,	
LD50 oral rat	> 4000 mg/kg bodyweight Animal: rat, Animal sex: male/female
LD50 Dermal Rabbit	> 13500 mg/kg 24 h
LC50 Inhalation - Rat	> 48170 mg/m ³ 4 h
Inhalation	Category 4

Judgement is based on the relevant ingredients.

Conclusion

Harmful if inhaled

Not classified as acute toxic in contact with skin

Not classified as acute toxic if swallowed

Corrosion/Irritation

Polymethylene polyphenyl isocyanate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remarks
Eye	Irritating; category 2					Literature Study	

ASMACO WINDOW & DOOR ALL SEASON PU FOAM

Safety Data Sheet

According to Regulation (EC) No.1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Skin	Irritating; category 2					Literature Study	
inhalation	Irritating; STOT SE cat.3					Literature Study	

Alkane, C14-17, chloro,

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remarks
Eye	Slightly irritating				Rabbit	Expert Judgement	
Skin	Slightly irritating	OECD 404	4 h	24;72 hours	Rabbit	Expert Judgement	

Classification is based on the relevant ingredients

Conclusion:

Causes skin irritation

Causes serious eye irritation

May causes respiratory irritation

Respiratory/Sensitisation

Polymethylene polyphenyl isocyanate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remarks
Skin	Sensitizing; category 1					Literature study	
Inhalation	Sensitizing; category 1					Literature study	

Alkane, C14-17, chloro,

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remarks
Skin	Nit sensitizing	Guinea pig maximization test		48 h	Guinea pig	Experimental Value	

Classification is based on the relevant ingredients

Conclusion:

May causes an allergic skin reaction.

May causes allergy or asthma symptoms or breathing difficulties if inhaled

May causes respiratory irritation.

Specific Target organ Toxicity

Polymethylene polyphenyl isocyanate

Route of Exposure	Parameter	Method	Value	Organ	Effect	Exposure Time	Species	Value determination
Inhalation			STOT RE cat.2					Literature study

Alkane, C14-17, chloro,

Route of Exposure	Parameter	Method	Value	Organ	Effect	Exposure Time	Species	Value determination
Oral (diet)	NOAEL	Equivalent to OECD 408	300 ppm	Liver; kidney	No adverse systemic effects	13 week (s)	Rat (male/female)	Experimental value
Oral (diet)	NOAEL	Equivalent to OECD 408	100 mg/kg bw/day	Kidney	No adverse systemic effects	13 week (s)	Rat (male/female)	Experimental value
Dermal								Data waiving
Inhalation								Data waiving

Classification is based on the relevant ingredients

Conclusion:

May causes damage to organs through prolonged or repeated exposure if inhaled.

ASMACO WINDOW & DOOR ALL SEASON PU FOAM

Safety Data Sheet

According to Regulation (EC) No.1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Carcinogenicity:

Polymethylene polyphenyl isocyanate

Route of Exposure	Parameter	Method	Value	Organ	Effect	Exposure Time	Species	Value determination
Unknown			Category 2					Literature study

Alkane, C14-17, chloro,

Route of Exposure	Parameter	Method	Value	Organ	Effect	Exposure Time	Species	Value determination
Oral	LOAEL	Equivalent to OECD 451	312 mg/kg bw/day		Carcinogenicity	104 weeks (5 day/week)	Rat M/F	Read-across
Oral	LOAEL	Equivalent to OECD 451	125 mg/kg bw/day		Carcinogenicity	104 weeks (5 day/week)	Mouse M/F	Read-across

SECTION 12. ECOLOGICAL INFORMATION:

12.1. Toxicity

Ecology - general

Polymethylene polyphenyl isocyanate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity other aquatic organisms	LC50		>1000 mg/l	96 h				Literature study
Toxicity aquatic micro-organisms	EC50	OECD209	>100 mg/l		Activated sludge			Literature study

Alkane, C14-17, chloro,

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	>10000 mg/l	96 h	Alburnus alburnus	Static system	Salt water	Experimental value
Acute toxicity invertebrates	EC50	OECD 203	0.0077 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value
Toxicity algae and other aquatic plants	EC50	OECD 201	>3.2 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long term toxicity fish	NOEC	OECD 204	>125 µg/l	14 days	Alburnus alburnus	Semi-Static system	Salt water	Experimental value
Long term toxicity aquatic invertebrates	NOEC	OECD 202	0.01mg/l	21 days	Daphnia magna	Static system	Fresh water	Experimental value

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic): Harmful to aquatic life with long lasting effects

Not rapidly degradable

SECTION 13. DISPOSAL CONSIDERATION:

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

ASMACO WINDOW & DOOR ALL SEASON PU FOAM

Safety Data Sheet

According to Regulation (EC) No.1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 05 01* (wastes not otherwise specified in 08: waste isocyanates).

16 05 04* (gases in pressure containers and discarded chemicals: gases in pressure containers (including halons) containing hazardous substances).

Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Recycle/reuse. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different

types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste.

Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent

risks of pollution or damage to people or animals. Specific treatment. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14. TRANSPORT INFORMATION:

14.1. UN Number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS, flammable
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

ADR/RID packing group	None
IMDG packing group	None
ICAO packing group	None
ADN packing group	None

14.5. Environmental hazards

Dangerous for the environment:	No
Marine pollutant:	No
Other information:	No supplementary information available Environmentally hazardous substance/marine pollutant

ASMACO WINDOW & DOOR ALL SEASON PU FOAM

Safety Data Sheet

According to Regulation (EC) No.1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.6. Special precautions for user

Overland transport

Classification code (ADR)	5F
Special provisions (ADR)	190, 327, 344, 625
Limited quantities (ADR)	11
Excepted quantities (ADR)	E0
Packing instructions (ADR)	P207, LP02
Special packing provisions (ADR)	PP87, RR6, L2
Mixed packing provisions (ADR)	MP9
Transport category (ADR)	2
Special provisions for carriage - Packages (ADR)	V14
Special provisions for carriage - Loading, unloading and handling (ADR)	CV9, CV12
Special provisions for carriage - Operation (ADR)	S2
Tunnel restriction code (ADR)	D

Transport by sea

Special provisions (IMDG)	63, 190, 277, 327, 344, 959
Limited quantities (IMDG)	SP277
Excepted quantities (IMDG)	E0
Packing instructions (IMDG)	P207, LP02
Special packing provisions (IMDG)	PP87, L2
EmS-No. (Fire)	F-D
EmS-No. (Spillage)	S-U
Stowage category (IMDG)	None
Stowage and handling (IMDG)	SW1, SW22
Segregation (IMDG)	SG69
MFAG-No	126

Air transport

PCA Excepted quantities (IATA)	E0
PCA Limited quantities (IATA)	Y203
PCA limited quantity max net quantity (IATA)	30kgG
PCA packing instructions (IATA)	203
PCA max net quantity (IATA)	75kg
CAO packing instructions (IATA)	203
CAO max net quantity (IATA)	150kg
Special provisions (IATA)	A145, A167, A802
ERG code (IATA)	10L

Inland waterway transport

Classification code (ADN)	5F
Special provisions (ADN)	190, 327, 344, 625
Limited quantities (ADN)	1 L
Excepted quantities (ADN)	E0
Equipment required (ADN)	PP, EX, A
Ventilation (ADN)	VE01, VE04
Number of blue cones/lights (ADN)	1

Rail transport

Classification code (RID)	5F
Special provisions (RID)	190, 327, 344, 625
Limited quantities (RID)	1L
Excepted quantities (RID)	E0
Packing instructions (RID)	P207, LP02
Special packing provisions (RID)	PP87, RR6, L2
Mixed packing provisions (RID)	MP9
Transport category (RID)	2
Special provisions for carriage – Packages (RID)	W14
Special provisions for carriage - Loading, unloading and handling (RID)	CW9, CW12

ASMACO WINDOW & DOOR ALL SEASON PU FOAM

Safety Data Sheet

According to Regulation (EC) No.1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Colis express (express parcels) (RID) CE2
Hazard identification number (RID) 23

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not acceptable

SECTION 15. REGULATORY INFORMATION:

15.1. Safety, health, and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content < 9 g/l

15.1.2. National regulations

Germany

VwVwS Annex reference

Water hazard class (WGK) 1, low hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal

Immission Control Act - 12.B ImSchV

Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen

None of the components are listed

SZW-lijst van mutagene stoffen

None of the components are listed

NIET-limitatieve lijst van voor de

voortplanting giftige stoffen – Borstvoeding

None of the components are listed

NIET-limitatieve lijst van voor de

voortplanting giftige stoffen – Vruchtbaarheid

None of the components are listed

NIET-limitatieve lijst van voor de

voortplanting giftige stoffen – Ontwikkeling

None of the components are listed

Denmark

Class for fire hazard

Class I-1

Store unit

1 liter

Classification remarks

F < Aerosol>; Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation

Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
Persons suffering from asthma or eczema and persons who have chronic lung diseases, skin or respiratory allergies to isocyanates should not work with the material
The requirements from the Danish Working Environment Authorities regarding work with epoxy resins and isocyanates must be observed during use and disposal
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2 Chemical Safety assessment

No chemical safety assessment has been carried out.

SECTION 16. OTHER INFORMATION:

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)

Acute toxicity (inhal.), Category 4

Acute Tox. 4 (Inhalation: gas)

Acute toxicity (inhalation: gas) Category 4

Aerosol 1

Aerosol, Category 1

Carc. 2

Carcinogenicity, Category 2

Eye Irrit. 2

Serious eye damage/eye irritation, Category 2

Flam. Gas 1

Flammable gases, Category 1

Press. Gas

Gases under pressure

Resp. Sens. 1

Sensitisation — Respiratory, Category 1

Skin Irrit. 2

Skin corrosion/irritation, Category 2

ASMACO WINDOW & DOOR ALL SEASON PU FOAM

Safety Data Sheet

According to Regulation (EC) No.1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Skin Sens. 1	Sensitisation — Skin, Category 1
STOT RE 2 S	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H229	Pressurised container: May burst if heated
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
EUH204	Contains isocyanates. May produce an allergic reaction

This product should be stored, handled, and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date of issue. However, no warranty or representation, express or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given for implied to practice any patented invention without a license. User is responsible for determining whether the ASMACO product is fit for a particular purpose and suitable for user's method of use or application. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices or from any hazard inherent in the nature of the product. This product must be stored, handled, and used in compliance with current regulation and laws. Furthermore, the specifications and description herein cannot be used to void a contract.