



Green Strength Instant Grab Adhesive Asmaco Pro Grab

Asmaco Pro Grab is an easy-to-use, high-strength, elastomeric product that can serve as both adhesive and sealant. It is a waterproof glue that instantly bonds, seals, and repairs virtually everything. This adhesive's instant grab capability holds objects in place and, in most cases, eliminates the need for fixtures. It cures in 24-48 hours and reaches maximum strength in 7 days. No need for screws or nails, it's perfect for all types of bonding, sealing and repairs. The special high-performance I-Tech Sealant formulation provides excellent underwater bonding and sealing capability and Asmaco Pro Grab can be used to seal water leakages without draining.



Product Details:

- Elastomeric
- Wet / Dry Applications
- Can Be Applied Under Water
- Strong Instant Grab
- Permanently Flexible
- Paintable
- Interior / Exterior
- Excellent Resistance to Chemicals & Microorganisms
- UV & Weather Resistant
- Non Sag
- Low Odor Adhesive
- VOC Compliant

Product Applications:

- RV, Marine, & Trailer
- Paneling Installation
- Countertops & Cabinets
- Backsplash Bonding
- Underwater Applications
- Window & Door Installation
- HVAC
- Emergency Repairs

Packaging:

- Colors: White
- 9.5 fl oz cartridges x 24 pcs



Technical Data

PROPERTIES	TYPICAL VALUES	TEST STANDARDS
Color	White	-
Consistency	Smooth Paste (Non Sag)	-
Solid Content	100%	-
Curing Rate	1/8" per 24 Hours (72° & 50% R.H.)	-
Service Temperature	-35°F - +140°F	-
Application Temperature	-35°F - +140°F	-
Density	1.6±0.02	ASTM D - 1475
Skin Over Time	9 - 11 Minutes	ASTM C 920 - 18 / ASTM C 679 - 15
Hardness Shore A	≈55	ASTM D 2240
Elongation @ Break	≥400%	ASTM D 412
Tensile Strength	≈2.5 N/mm ²	ASTM D 412
Tear Strength	≈9.0 N/mm	-
UV Resistance	Good	-
Bonding Under Water	Good	-



Adhesion:

We recommend a compatibility test prior to painting and adhesion test prior to application.

Adheres to: most porous and non-porous substrates including most metals, wood, foam, rubber, tile, ceramic, marble, porcelain, glass, granite, brick, concrete, stucco, plaster, stone, masonry, drywall, fiberglass, some plastics & vinyl, composites, PVC, EPS, EPDM roofs, and more.

Application Instructions

Apply product when ambient temperatures are above 40°F.

Surface Preparation:

Thoroughly remove all residual dirt and old sealant and clean surface with a degreasing solvent. Immediately wipe with another clean cloth to remove residual solvent and dirt.

Masking:

Use masking tape to achieve a clean and professional appearance. Protect surrounding areas from excess sealant to reduce cleanup.

Applying The Adhesive:

Cut the nozzle at a 45° angle and attach to cartridge. Puncture inner seal. Place into caulk gun. Apply the sealant in a continuous bead, making sure to maintain even pressure. For large surfaces, apply in vertical strips or dots at regular intervals.

Position The Materials:

Quickly bring the surfaces together, applying firm pressure to ensure full contact with the adhesive. Adjust as needed before the adhesive begins to set.

Instant Grab:

The adhesive's instant grab feature will hold the objects in place. For heavier items, temporary support may be needed until the adhesive cures.

Curing Time:

Allow the adhesive to cure for 24-48 hours. Full strength is typically reached within 7 days. During curing, avoid disturbing the bonded area to ensure a strong and lasting bond.

Finishing:

- **Paint if necessary:** Once cured, the adhesive can be painted to match the surrounding area.
- **Clean Up:** Clean any excess adhesive with a suitable solvent before it dries. Tools and hands can be cleaned with soap and water.

Under Water Application:

Asmaco Pro Grab Adhesive can be applied directly to wet surfaces or even underwater. Follow the same application steps, ensuring that the surfaces are firmly pressed together.



Storage & Disposal

Reseal cartridge for storage and future use. Store opened and unopened containers in a cool, dry, well-ventilated area away from heat, sparks and direct sunlight. Elevated temperatures or extreme cold will reduce the shelf life of the product.

Dispose of product in accordance with local government disposal guidelines. Cured material may be disposed of in the trash.

Health & Safety

Direct contact with uncured sealant irritates eyes and may irritate skin. Exposure to vapor may irritate eyes, nose and throat. Keep out of reach of children. Avoid skin and eye contact. In case of eye contact, flush eyes with warm water for 15 minutes and seek medical attention. For skin contact, remove sealant with a clean paper towel. If swallowed do not induce vomiting, seek medical attention. Asmaco Pro Grab is manufactured for professional use only. Refer to Safety Data Sheet (SDS) for further information.

Limited Warranty

Manufacturer warrants that this product, when used as directed, will meet the above specifications. If not satisfied, return with proof of purchase for refund. This is the sole and exclusive remedy and Manufacturer shall not be liable for any damages in excess of the purchase price. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS. This Limited Warranty gives you specific legal rights, which vary from state to state. For warranty assistance, contact Anchor Allied USA

This information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory LLC's control, we can accept no liability for the result obtained. Anchor Allied Factory LLC's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory LLC will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.

All ANCHOR ALLIED FACTORY LLC data sheets are updated on regular basis. The Technical data sheet supersedes all previous editions relevant to this product. It is the user's responsibility to obtain the recent version.