

**All-Purpose Solvent Based Adhesive****Asmaco Pro N3**

Asmaco Pro N3 (No Need Nails) is an all-purpose solvent based grab adhesive used for bonding subfloor, wall panels, profiles skirting boards, stair nosing's, tiles, parquet planks, fabric, mirrors, veneers, MDF, insulating panels (including polystyrene), EPS, all metal surfaces, gypsum, concrete, bricks, and much more onto almost any type of substrates. This product is suitable for interior and exterior application.

**Product Details:**

- Superior Bond Strength to Common Building Materials
- Increases Structural Integrity of Walls, Decks, & Subfloors
- Reduces Nailing
- Fills Gaps & Irregularities
- High Filling Capacity
- Helps Reduce Floor Squeaks
- Fast Setting
- Increases Floor Rigidity
- Ideal for Plywood, Particleboard and OSB
- No Rusting
- No Substrate Piercing

Product Applications:

- OEM Bonding
- Interior / Exterior Floors, Walls, and Decks
- Bonding Mirrors
- Filling Irregularities Between Uneven Materials Up To 1/4"

Packaging:

- Colors: Cream
- 9.5 fl oz cartridges x 24 pcs



Technical Data

TYPICAL PROPERTIES	
Composition	Synthetic Rubber Resin
Consistency	Smooth & Pasty
Color	Cream
Viscosity	4000 PS (Approx.)
Open Time	5 - 10 Minutes
Setting Time	Immediate Bonding
Initial Cure	1 Hour
Full Cure	48 Hours
Working Temperature	Ambient Conditions

Application Instructions

Apply product when ambient temperature is between 50F° and 140F°.

Typical Bonding:

Used for general purpose bonding of construction materials. Apply Asmaco Pro N3 to the material in parallel linear beads 6 inches apart. For smaller panels, apply individual beads. Place the substrates to be bonded into position and press firmly over entire surface. Clamp for a minimum of 8 to 10 minutes to insure ideal bonding strength.

Power Bonding Method:

For bonding heavy panels or onto impervious substrates, follow the above mentioned application method, but after pressing the piece into position, pull both surfaces apart so that the adhesive is transferred to other substrate. Wait for 5 to 10 minutes and place the pieces immediately into position and press firmly together. The bond is immediate.

Full cure for both application methods is 24 to 48 hours.

Remarks:

- Work in a dust free environment
- Do not use on a wet / damp substrate
- Do not use when temperatures are below 50°F

Cleaning:

- Can be cleaned with acetone or mineral spirits



Storage & Disposal

Reseal cartridge for storage and future use. Store opened and unopened containers in a cool, dry, well-ventilated area away from heat, sparks and direct sunlight. Elevated temperatures or extreme cold will reduce the shelf life of the product.

Dispose of product in accordance with local government disposal guidelines. Cured material may be disposed of in the trash.

Health & Safety

Direct contact with uncured sealant irritates eyes and may irritate skin. Exposure to vapor may irritate eyes, nose and throat. Keep out of reach of children. Avoid skin and eye contact. In case of eye contact, flush eyes with warm water for 15 minutes and seek medical attention. For skin contact, remove sealant with a clean paper towel. If swallowed do not induce vomiting, seek medical attention. Asmaco Pro N3 is manufactured for professional use only. Refer to Safety Data Sheet (SDS) for further information.

Limited Warranty

Manufacturer warrants that this product, when used as directed, will meet the above specifications. If not satisfied, return with proof of purchase for refund. This is the sole and exclusive remedy and Manufacturer shall not be liable for any damages in excess of the purchase price. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS. This Limited Warranty gives you specific legal rights, which vary from state to state. For warranty assistance, contact Anchor Allied USA

This information and data contained in the product data sheet is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of the product for usage. Since the supplier cannot know all the uses, or the conditions of use to which the product may be exposed, no warranties concerning the fitness or suitability for particular use or purpose are made. It is the user's responsibility to thoroughly test any purposed use of our products and independently conclude satisfactory performance in the application likewise if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-Warranty: Because the storage, handling and application of the material is beyond Anchor Allied Factory LLC's control, we can accept no liability for the result obtained. Anchor Allied Factory LLC's sole limited warranty is the product meets the manufacturing specifications in effect at the time of shipment. There is no warranty or merchantability or fitness for use, nor any expressed or implied warranty. Anchor Allied Factory LLC will not be liable for any incidental and consequential damage of any kind. The exclusive remedy for breach of such limited warranty is a replacement of any product shown to be other than warranted. Suggestions of uses should not be taken as inducement to infringe any patents.

All ANCHOR ALLIED FACTORY LLC data sheets are updated on regular basis. The Technical data sheet supersede all previous editions relevant to this product. It is the user's responsibility to obtain the recent version.